




Crown (A) pushed down
Position 1



Crown (A) pulled one "click" out
Position 2



Crown (A) pulled two "clicks" out
Position 3



Thank you for choosing a time-piece from our 925 Sterling Silver collection
(Series: SL-3136S, SL-3136 RG, 2121 SB, 2121 SS, 2121 RG, 2024 SR).

Your watch is fitted with Swiss-made ETA 2836-2 Automatic movement and an [Incabloc® shock-absorber](#) device. The inner mechanism of the watch has a free swinging rotor that keeps the mainspring wound via the motion of your wrist. A watch fitted with an automatic winding movement is rewound by the regular movements of your wrist. *Once fully wound, your watch will continue to keep time for approximately 38 hours after removing it from your wrist. Beyond this time, the watch will stop. You will then need to rewind it manually turning the crown (A) clockwise (approximately 20 turns) to provide it with the necessary power reserve. After that, your daily activity should wind the watch sufficiently to keep it running at night when it is not being worn. You should wear your watch everyday to ensure optimal rewinding.*

Note: As this is a mechanical watch, quartz watch accuracy cannot be expected.

Setting the Time and Date

Setting the Time and Date

Important note: Do not change the date between 8 p.m. and 2 a.m. as this may damage the movement. This is when the pinions are being repositioned to carry out the automatic date change.

1.

Pull out the crown (A) to Position "2" (one "click" out). Rotate the crown (A) clockwise until the date shows one day earlier than the date you want to set.

Rotate the crown (A) counter-clockwise until the day shows one day earlier than the day you want to set.

Pull out the crown (A) to Position "3" (two "clicks" out). The seconds hand is stopped.

Set the time by turning the crown (A) counter-clockwise to move the hour and minute hands forward. Turn the watch hands past 12 once if you're setting the watch for a P.M. time.

2.

Once you have set the time or date, return the crown (A) to the pushed down Position "1" by pressing it against the case.

Remark:

You can synchronize the seconds hand with an official time signal (radio/ TV/Internet). When the crown (A) is pulled out in Position “3” (two “clicks” out), the seconds hand is stopped. As soon as the time setting has been synchronized, return the crown (A) to the pushed down position “1” by pressing it against the case.

Important Note: In order to insure that your watch remains water-resistant, it is important that crown (A) is always returned to the pushed down position “1”.

Specifications:

Case/Case back

– Solid 925 Sterling Silver

Glass

– Curved Sapphire Crystal

Movement

– Automatic ETA 2836-2

Water-Resistance

– 30M/99FT

Servicing your Xezo Automatic watch

Although components in your watch have been manufactured from first-rate materials, certain parts are subject to natural wear and tear. It is vital that all moving parts are properly lubricated at all times and that the watch is cleaned at regular intervals to remove dirty oil.

We therefore, recommend that you have your watch serviced about once every 3-5 years. Contact us for after-sales service.

<http://www.xezo.com>